

126B3

What Is Claimed Is:

1 ~~1. A wire harness comprising a plurality of~~
2 ~~partial harnesses,~~

3 wherein each of the partial harnesses is
4 arranged such that opposite end portions of a
5 plurality of electric wires having terminals at
6 ends thereof are retained in advance in U-shapes
7 with predetermined intervals provided so as to
8 correspond to a plurality of connectors into which
9 the terminals are inserted, by a plurality of wire
10 clamps juxtaposed at equal pitches on a wire
11 clamping bar, and

12 wherein the terminals at the ends of the
13 plurality of electric wires in each of the partial
14 harnesses are inserted into terminal accommodating
15 chambers of predetermined connectors selected from
16 the plurality of connectors, thereby aggregating
17 the plurality of partial harnesses into a combined
18 unit.

1 2. A wire harness according to claim 1, wherein
2 the plurality of connectors into which the
3 terminals are inserted comprise at least one of
4 connectors proper to a relevant partial harness
5 into which only the terminals of the plurality of
6 electric wires making up each of the partial
7 harnesses are inserted and hybrid connectors into
8 which the terminals of the electric wires of two or
9 more of the partial harnesses are inserted in mixed
10 form.

1 3. A wire harness according to claim 1, wherein
2 the proper connector is fitted in advance to the
3 ends of predetermined ones of the electric wires of
4 ~~each of the partial harnesses.~~

1 4. A wire harness according to claim 1, wherein
2 the hybrid connector is fitted in advance to the
3 ends of the electric wires of one or two of the
4 partial harnesses selected from the plurality of
5 partial harnesses.

1 5. A wire harness according to claim 1, wherein
2 each of the partial harnesses includes electric
3 wires to stripped ends of which terminals are
4 unconnected, and the stripped ends thereof are
5 jointed in the aggregated state.

1 6. A method of manufacturing a wire harness from
2 the plurality of partial harnesses, comprising:

3 a step of transferring a wire clamping bar
4 which holds an initial one of the partial harnesses
5 to a wire-harness fabricating station;

6 a step of inserting the terminals at ends of
7 a plurality of electric wires consecutively into
8 predetermined terminal accommodating chambers of
9 predetermined ones of the connectors selected from
10 the plurality of connectors set on a connector
11 receiving jig in the wire-harness fabricating
12 station;

13 a step of removing the wire clamping bar which
14 has been emptied; and

15 repeating the steps of transferring, inserting
16 and removing consecutively for ensuing ones of the
17 partial harnesses.

1 7. A method of manufacturing a wire harness
2 according to claim 6, further comprising a step of
3 transferring a proper connector fitted in advance
4 to ends of predetermined ones of the electric wires
5 of each of the partial harnesses to the connector
6 receiving jig in the wire-harness fabricating
7 station.

1 ~~8. A method of manufacturing a wire harness~~
2 according to claim 6, further comprising a step of
3 collectively jointing, in the wire-harness
4 fabricating station, two or more stripped portions
5 of the electric wires included in each of the
6 partial harnesses.

1 9. A method of manufacturing a wire harness
2 according to claim 7, further comprising a step of
3 collectively jointing, in the wire-harness
4 fabricating station, two or more stripped portions
5 of the electric wires included in each of the
6 partial harnesses.

1 10. A method of manufacturing a wire harness
2 according to claim 6, further comprising a step of
3 jointing, in the wire-harness fabricating station,
4 stripped portions of the ends of the electric wires
5 included in each of the partial harnesses, such
6 that the stripped portions are consecutively
7 superposed one on top of another each time each of
8 the partial harnesses is transferred to the wire-
9 harness fabricating station.

1 11. A method of manufacturing a wire harness
2 according to claim 7, further comprising a step of
3 jointing, in the wire-harness fabricating station,
4 stripped portions of the ends of the electric wires
5 included in each of the partial harnesses, such
6 that the stripped portions are consecutively
7 superposed one on top of another each time each of
8 the partial harnesses is transferred to the wire-
9 ~~harness fabricating station.~~

1 12. An apparatus for manufacturing a wire harness,
2 comprising:

3 a wire-harness fabricating station for forming
4 a single wire harness from partial harnesses, the
5 wire-harness fabricating station having a connector
6 receiving jig which detachably holds a plurality of
7 proper connectors and a plurality of hybrid
8 connectors.

1 13. An apparatus for manufacturing a wire harness
2 according to claim 12, wherein the wire-harness
3 fabricating station comprises a connector
4 transferring device for transferring, to the
5 connector receiving jig, ones of the proper
6 connectors and hybrid connectors which are fitted
7 in advance to the partial harness.